





EB-20M-2DS ELECTRIC HYSTERESIS BRAKE
PERFORMANCE CURVE
TORQUE VS. CURRENT



NOTE:

1. ACTUAL CURVE MAY VARY. THE TORQUE AT THE RATED CURRENT IS THE MINIMUM GUARANTEED TORQUE AT THAT CURRENT. TYPICAL BRAKES CAN BE 10-25% OVER RATED TORQUE, BUT THOSE RESULTS ARE **NOT** GUARANTEED.

THIS DRAWING IS THE PROPERTY OF MAGNETIC TECHNOLOGIES LTD. AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT SHALL NOT BE LENT, COPIED, REPRODUCED NO DISCLOSED TO ANY OTHER PERSON, IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF MAGNETIC TECHNOLOGIES LTD.

USED ON		SCALE		MATERIAL		MAGNETIC 43 TOWN FOREST ROAD OXFORD, MA 01540			
EB-20M-2DS									
UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES TOLERANCES: DECIMAL: .XX ± .01 .XXX ± .005 ANGULAR: ± 1° GEN. CONCENTRICITY: .001 T.I.R. MACH. FILLETS: .010 R MACH. EDGES: .015 R OR CHMF. UNSPECIFIED RADII: .015 R IN MICROINCHES RMS 32 GEOMETRIC: TO MIL-ST'D. 8 REMOVE ALL BURRS & SHARP EDGES				FINISH		DESCRIPTION			
				DRAWN					
				KJM 2-13-12		TECHNICAL DATA			
				CHECKED					
				WEIGHT:		DWG. NO.		REV.	
SIZE: B		ISO 9001:2015 CERTIFIED 		EB-20M-2DS					